

































45 mm base extrusion	Type		Weight [kg/m]	I _{x,y} [cm ⁴]	W _{x,y} [cm ³]	Page
Beam extrusion 45x180	Type E01-16		6.4	743.74, 57.06	82.64, 25.36	76
Light extrusion 90x90	Type E02-5		4.7	160.09	35.58	77
Base extrusion 90x90	Type E01-4		6.1	205.78	45.73	78
Beam extrusion 90x135	Type E01-13		8.1	618.00, 300.57	98.56, 66.79	79
Beam extrusion 90x180	Type E01-5		12.1	1525.63, 443.9	169.51, 98.64	80
40 mm base extrusion	Type		Weight [kg/m]	I _{x,y} [cm ⁴]	W _{x,y} [cm ³]	Page
Four sided softline extrusion 40x40	Type C10-0		1.6	9.6	4.75	81
Four sided softline extrusion 40x80	Type C10-3		2.8	69.73, 18.52	17.43, 9.26	81
Four sided softline extrusion 80x80	Type C10-4		4.4	119.40	29.85	82
Super lightweight extrusion 40x40	Type C03-1		1.3	8.20	4.10	83
Lightweight extrusion 40x40	Type C02-1		1.5	9.35	4.67	83

Technical data

40 mm base extrusion

40 mm base extrusion	Type		Weight [kg/m]	I _{x,y} [cm ⁴]	W _{x,y} [cm ³]	Page
Base extrusion 40x40	Type C01-1		2.0	11.70	5.75	84
Face extrusion 40x40	Type C01-8		2.0	11.66, 11.67	5.78, 5.83	84
Corner extrusion 40x40	Type C01-7		1.5	9.21	4.53	85
Double face extrusion 40x40	Type C02-4		1.5	9.56, 9.21	4.78, 4.60	85
Face panel extrusion 40x40	Type C04-2		1.6	9.13, 9.92	4.57, 4.96	86
Corner panel extrusion 40x40	Type C04-7		1.6	9.53	4.76	86
45° angle extrusion	Type C04-4		1.5	8.46, 9.11	3.01, 3.44	87
40x45° angle extrusion	Type C02-8		1.2	6.30	2.70	87
Softline extrusion 40x40	Type C03-8		1.3	6.70	2.97	88
Light extrusion 40x80	Type C02-3		2.8	64.90, 17.70	16.23, 8.85	89
Base extrusion 40x80	Type C01-3		3.7	81.95, 22.74	20.49, 11.37	89
Face extrusion 40x80	Type C01-5		2.6	64.40, 17.20	16.10, 8.60	90

40 mm base extrusion	Type		Weight [kg/m]	I _{x,y} [cm ⁴]	W _{x,y} [cm ³]	Page
Light extrusion 40x120	Type C03-9		4.0	203.49, 25.75	33.91, 12.87	90
Beam extrusion 40x120	Type C01-9		5.3	258.52, 33.43	43.09, 16.72	91
Beam extrusion 40x160	Type C02-9		7.0	592.79, 44.36	74.09, 22.18	92
L-shaped extrusion 80x80x40	Type C01-6		5.3	109.18	23.56	93
Corner extrusion 80x80x40 round	Type C03-6		3.6	76.40	19.10	94
Base extrusion 80x80	Type C01-4		6.0	154.70	38.68	95
Lightweight extrusion 80x80	Type C03-4		4.4	115.66	28.92	95
Corner extrusion 80x80	Type C03-7		4.5	117.70	29.43	96
Beam extrusion 80x120	Type MC1-2		8.4	451.20, 219.76	75.20, 54.94	97
Heavy duty extrusion 80x160	Type MC1-9		11.0	1018.98, 296.53	112.37, 74.13	98

Technical data